

ELETTROPOMPA SOMMERSA MULTISTADIO MULTISTAGE SUBMERSIBLE PUMP

LIMITI D'IMPIEGO

- Temperatura liquido fino a 35°C
(per un uso domestico secondo EN 60335-2-41)
Temperatura max. liquido: 35°C (per altri impieghi)
- Profondità d'immersione 10 mt.
- Partenza/ora 30 max.
- Passaggio solidi Ø 3 mm
- Livello min. d'aspirazione 60 mm

MOTORE

- Motore elettrico ad induzione a 2 poli
(n = 2850 min⁻¹)
- Protezione amperometrica a riarmo automatico incorporata
- Isolamento Classe F
- Protezione IP 68
- Cavo alimentazione 10 mt.
- Galleggiante di serie

MATERIALI

- Corpo pompa Acciaio Inox
- Griglia Noryl
- Girante e diffusori Noryl
- Supporti Alluminio
- Albero Acciaio Inox
- Corpo motore Alluminio
- Tenuta meccanica

OPERATING CONDITIONS

- Liquid temperature up to 35°C
(for home use according to EN 60335-2-41)
Temperature max. liquid: 35°C (for other uses)
- Submersion depth 10 mt.
- Start/hour 30 max
- Grain size inlet Ø 3 mm
- Min. suction level 60 mm

MOTOR

- Two-Pole induction motor
(n = 2850 min⁻¹)
- Built-in over load motor protector with automatic reset
- Insulation Class F
- Protection IP 68
- Power cable 10 mt.
- Standard floater

MATERIALS

- External pump body Stainless Steel
- Suction strainer Noryl
- Impeller and diffusors Noryl
- Bearing brackets Aluminium
- Shaft Stainless Steel
- Motor housing Aluminium
- Mechanical seal



SMC 1103

TIPO - TYPE	
P1	1100 W
Voltage	230 V
Frequency	50 Hz
Ampere	5 A
Q max.	130 l/1'
H max.	38 m
DNM - DNA	1"
Dimensions (P x L x H)	188 x 230 x 430 mm
Weight	12,8 kg

